

FC-5S fibre cleaver

Table top cleave tool with offcut collector



Single fibre adaptor for..

- rectangular section drop cable
- 250um primary coated fibre
- 900um secondary coated fibre
- 3mm ruggedised cord



Offcut collector
for fibre sharps

Stable base for table top operation

FIBRE TYPES	FC-5S
USE WITH FIBRE HOLDERS	Silica glass: 125um SMF, MMF, NZDSF, BIF and others
CLEAVE LENGTH 250um	Yes
CLEAVE LENGTH 900um	5 to 20mm with single fibre adaptor, 10mm with fibre holders
CLEAVE LENGTH DROP CABLE, 3MM CORD (Note 1)	10 to 20mm with single fibre adaptor, 10mm with fibre holders
HARD CARRYING CASE	12 to 20mm with single fibre adaptor
FIBRE NUMBER	Included
SINGLE FIBRE ADAPTOR	1
	Yes, AP-FC5S
	Accepts 250um and 900um coated fibre and rectangular drop cable
DIMENSIONS (mm)	93x72x66
WEIGHT	190g
OFFCUT COLLECTOR	Yes, TR-FC-5S
OPERATING CONDITIONS	Temperature -10°C to 50°C Humidity ≤95% non-condensing
STORAGE CONDITIONS	Temperature -40°C to 80°C Humidity ≤95% non-condensing
FIELD REPLACEABLE BLADE	Yes, FCP-20BL
BLADE LIFE (Note 2)	48,000 fibres - 24 blade positions, 2000 cleaves per position

Note 1: between the end of the sheath / cable and the cleave point
 Note 2: not guaranteed. It may vary with operating conditions

Sumitomo Electric reserves the right to alter product specifications without notice E&OE

Sumitomo Electric Europe Ltd www.sumielectric.com seel@sumielectric.com

Document part number TZA013DO0006-00 Document release date 2016-10-18

© Sumitomo Electric Europe Ltd